


D E C K O

D O O R S



# FEATURES



Made-to-measure available

# PERFORMANCE



STANDARD	AIR INFILTRATION EXFILTRATION	WATER RESISTANCE	DESIGN PRESSURE	PRIMARY DESIGNATOR
AAMA/WDMA/CSA 101/I.S.2/A440-11	A3	400 Pa (8,35 psf)	1920 Pa (40 psf)	R-PG40-SD 1793 X 2055 mm (~ 71 X 81")

# OPTIONS

## ENERGY-EFFICIENT DOUBLE-PANE GLASS

## CLEAR OR ENERGY-EFFICIENT TRIPLE-PANE GLASS




7/8" sealed unit



1 1/4" sealed unit

## PAINT



Doors can be painted to your interior and exterior colour specifications.

## BRICK MOULD



1 1/2" wide aluminum brick mould with a 1 1/8" projection.

PVC brick mould with a 1 1/8" projection available in 1 1/2" and 4" widths.

## GRILLS



The colours illustrated in this brochure are for illustration only and may differ from actual colours. Some options are not available on all doors.

CONTEMPORARY  
EURO HANDLES



White Satin Nickel Black

CONTEMPORARY  
9100 HANDLE



Exterior Interior

EURO  
HANDLES



Brass Bright Chrome Brushed Chrome Black Nickel Dark Oil-Rubbed Bronze Antique Brass Satin Nickel

KEY LOCK



SECURITY BAR



MULTIPOINT HANDLE



FOOT LOCK



EMBOSSED  
TERRACE PANELS



FAKE  
MULLIONS



SIDLIGHT  
AND TRANSOMS



# DIMENSIONS

## Legend S

WIDTH	2 LIGHTS				3 LIGHTS			4 LIGHTS	
	5'	6'	7'	8'	9'	10'	12'	9'	12'
HEIGHT					OXO	OXO	OXO	OXXO	OXXO
					106 3/4" 2,710 mm	124 3/4" 3,167 mm	142 3/4" 3,625 mm		
					79 1/2"* 2,019 mm	XO/OX	XO/OX	XO/OX	XO/OX
81" 2,057 mm	58 5/8" 1,489 mm	70 5/8" 1,794 mm	82 5/8" 2,099 mm	94 5/8" 2,403 mm	106 7/16" 2,703 mm	124 7/16" 3,160 mm	142 7/16" 3,618 mm	XOOX	XOOX
95 1/2"* 2,426 mm					XOX	XOX	XOX		
					103 3/16" 2,621 mm	121 3/16" 3,078 mm	139 3/16" 3,535 mm		

\* Energy-efficient glass only.

O: fixed X: open



[PORTESDECKO.COM](http://PORTESDECKO.COM)

The manufacturer reserves the right to make changes without notice.

COMPATIBLE PRODUCTS

**SONIPLASTICS**  
CREATING TRANSFORMING INNOVATING SINCE 1970

[SONIPLASTICS.COM](http://SONIPLASTICS.COM)

© 2017 — All rights reserved. 10/2017 version